



SPECIFICATION SHEET

34-774B



MAXIFLEX® ELITE™ ULTRA LIGHT WEIGHT SEAMLESS KNIT NYLON GLOVE WITH NITRILE COATED MICRO-FOAM GRIP ON PALM & FINGERS

- At a weight of 14 grams, our lightest and thinnest MaxiFlex when extreme dexterity is needed
- 30% thinner than traditional foam nitrile gloves
- Patented micro-foam nitrile coating offers 360° breathability
- Touch screen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Ultra light-weight liner creates smooth and rounded fingertips maximizing sensitivity, dexterity, and tactility
- Minimal penetration (strike through) leaving only the soft liner resting against the skin
- Anti-static - complies with EN 16350-2014 for electrostatic protective gloves
- Silicone Free
- Complies with FDA food handling requirements 21 CFR, Part 177

APPLICATIONS

- General assembly
- Micro-engineering
- Automotive components
- Painting
- Horticulture

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	Seamless nylon with Spandex® liner; micro-foam nitrile coating					
COLOR	■ Black / Gray					
CUFF STYLE	Continuous Knit					
SIZES	XS-XXL					
PACKAGING	12 pair per dozen, 12 dozen per case					
CASE	19.7" x 11.6" x 10.6" / 50cm x 29.5cm x 27cm					
CASE WEIGHT	XS	S	M	L	XL	XXL
	9.8 lbs 4.5 kg	11 lbs 5 kg	11.7 lbs 5.32 kg	12.3 lbs 5.6 kg	13 lbs 5.9 kg	13.7 lbs 6.2 kg
COO	Sri Lanka					



BARCODES


ITEM	PAIR	DOZEN	CASE
■ 34-774B/XS	---	10616314289511	20616314289525
■ 34-774B/S	---	10616314289528	20616314289525
■ 34-774B/M	---	10616314289535	20616314289532
■ 34-774B/L	---	10616314289542	20616314289549
■ 34-774B/XL	---	10616314289559	20616314289556
■ 34-774B/XXL	---	10616314289566	20616314289563

DIMENSIONS (in/cm)

	XS	S	M	L	XL	XXL
A	7.7 / 19.5	8.1 / 20.5	8.5 / 21.5	8.7 / 22.0	8.9 / 22.5	9.1 / 23.0
B	3.1 / 8.0	3.2 / 8.2	3.3 / 8.4	3.7 / 9.4	3.8 / 9.7	3.9 / 10.0
H	■ Blue	□ White	■ Green	■ Brown	■ Yellow	■ Gray

PERFORMANCE PROPERTIES

EN388: 4121A						
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (TDM-100)	A	B	C	D	E	F



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.