

**Models: FP3734-5N, 5C, 5S**



## Description

Zinc plated steel swivel anchorage with hybrid and semi-permanent and permanent D-ring. The D-ring is reusable. It can be installed on concrete or on a steel structure, it is offered with a variety of fastening set according to your installation needs. Approved for a capacity of 22kN (5000lbs).

The hardware can be ordered separately (steel FP3734-5SB), (concrete FP3734-5CB)

<b>SIZE</b>	<i>Bolt 4 ½ '' , Ring 2 ¼ '' Diam, plate 3 '' diam. Overall length 8 ''</i>	<b>COUNTRY OF ORIGIN</b>	USA
<b>TYPE</b>	Anchor	<b>MATERIALS</b>	Zinc plated steel
<b>CLASSIFICATION</b>		<b>MAX WORK LOAD</b>	310lbs
<b>COMPLIANCE</b>	CSA Z259.15 / ANSI Z359.1-07, ANSI Z359.7-11	<b>WEB MIN TENSILE</b>	N/D
<b>COMPONENTS CLASSIFICATION</b>	Certifié à CSA Z259.15-12 / ANSI Z359.1-07 and ANSIZ359.7-11	<b>D-RING MIN TENSILE</b>	5000lbs (22 kN)
<b>COLOR</b>	Golden	<b>HARDWARE MIN TENSILE</b>	5000lbs (22 kN)
		<b>WEIGHT</b>	1.4 lbs ( 681g)

Training and appropriate use: Please refer to the product manual included with the products before using them. Not following the manufacturer's instructions can create a risk of injury, illness or even death.  
For more information: 1-877-446-3278

revision: August 20, 2018

### Head Office

2477, Michelin, Laval, Qc H7L 5B9  
T: (450) 622-7374/ 1 877 446-3278  
F: (450) 622-2243/ 1 877 463-2789

### Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3  
T: (905) 565-9990  
F: (905) 565-9906

