

Model: FP09R



Description:

Reusable Roof Anchor. Designed for attachment to a suitable structure on residential roofing and commercial use. Anchor Structure must meet local strength requirements for fall arrest.

Maximum free fall distance should be limited to 6 feet (1.8 meter). All 10 screws need to be used.

Choose CSA certified full body harness, energy absorber, lifeline and components when using Roof Anchor.

SIZE	<i>Unique</i>	MADE IN	<i>Taiwan</i>
TYPE	<i>Reusable Roof Bracket</i>	MATERIALS	<i>High Strength Steel</i>
CSA CLASS	<i>NA</i>	MAX WORK LOAD	<i>Single Person Usage Only (400 lbs)</i>
DIMENSION	<i>14.28 in x 3.01 in (362 mm x 76 mm)</i>	WEB MIN TENSILE	<i>6000 lbs (27 kN)</i>
COLOR	<i>Red Painted</i>	BRACKET TENSILE STRENGTH	<i>5000 lbs (22.2 kN)</i>
SCREWS	<i>8 x2-1/2" (10 pieces)</i>	WEIGHT	<i>39.5 oz (1120 g)</i>

Training and Proper Use: Please refer to product manual included with the products prior to use.
For Additional Information: 1-877-446-3278

Revision 2, August 9, 2023

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374/ 1 877 446-3278
F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
T: (905) 565-9990
F: (905) 565-9906