

Model: Kilimanjaro
HP641/HP641R/HP641RV



Description:

The Kilimanjaro series (HP641, HP641R & HP641RV) of hardhats has a contemporary design with a full brim for extra protection against UV rays and falling debris. It is versatile to fit a variety of users with their variety of applications. The Kilimanjaro series is widely used in harsh environments like mining, oil & gas, and forestry. It is equipped with accessory slots. It also offers the choice between ratchet or pin-lock adjustments of a nylon-webbing 4-points suspension. It is also available with ventilation holes for hot environments. The Kilimanjaro series is ideal for environments where vertical impact on the head is a risk.

Product Number	Description	Order Multiples	Case Quantity	Case Dimensions	Case Weight
HP641	4-points nylon suspension, pin-lock adjustment, CSA & ANSI Type 1, Class E	12	12	62.9 X 34.3 X 57.8 cm 24.75" X 13.5" X 22.75"	6.3 kg. 13.9 lbs.
HP641R	4-points nylon suspension, ratchet adjustment, CSA & ANSI Type 1, Class E	12	12	62.9 X 34.3 X 57.8 cm 24.75" X 13.5" X 22.75"	7 kg. 15.4 lbs.
HP641R	4-points nylon suspension, ratchet adjustment, Ventilation holes, CSA & ANSI Type 1, Class C	12	12	62.9 X 34.3 X 57.8 cm 24.75" X 13.5" X 22.75"	7 kg. 15.4 lbs.

SIZE	N/A	COUNTRY OF ORIGIN	Canada
TYPE	CSA Type 1 & ANSI Type I	MATERIALS	Shell: HDPE Suspension: HDPE/NYLON webbing
CLASSIFICATION	HP641 & HP641R = Class E (dielectric) HP641RV = Class C (Conductive)	WEIGHT	HP641R & HP641RV: 561 g HP641: 490 g
COMPLIANCE	CSA Z94.1-15 & ANSI Z89.1-2014	THERMAL RESISTANCE	Softening Temp.: 262°F (128°C)
COMPONENT CLASSIFICATION	N/A	REPLACEMENT SUSPENSION	HP641 = HP641S (CSA & ANSI) HP641R & HP641RV = HP641RS (CSA & ANSI)
COLOR	White / yellow / orange / dark green / sky blue / navy blue / grey / black / red / Hi Viz orange / Hi Viz yellow		

Revision: Jan - 2019

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374 / 1 877 446-3278
F: (450) 622-2243 / 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
T: (905) 565-9990
F: (905) 565-9906