

# SPECIFICATION SHEET STYLE: GP34874V





Seamless Knit Nylon/Elastane Glove with Nitrile Coated MicroFoam Grip on Palm & Fingers -Vend-Ready Sustainable Cardboard Packaging

- · Vend pack ready for Personal Protective Equipment (PPE) vending machines in the industrial workplace
- MicroFoam Nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- 360° Breathability Patented micro-foam nitrile coating offers 360° breathability, making it the most breathable glove on the market
- 25% Thinner Than most foam nitrile gloves on the market while offering twice the mechanical performance

## **Applications**

- Maximum Breathability, Comfort and Durability
- Handling, Assembly and Sorting of Small Parts and Materials
- Finishing and Parts Inspection











#### **Technical Data**

| Color                | Gray  |
|----------------------|---|
| Sizes Available      | XS-2XL  |
| Packaging            | Vend Packed                                       |
| Packed               | 144 Pair/Case                                     |
| Case Dimensions (cm) | 50.00 x 29.50 x 27.00                             |
| Case Weight (kg)     | 8.15  |
| Country of Origin    | Sri Lanka   |
| Liner Material       | Nylon, Elastane                                   |
| Coating              | Nitrile   |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers                                    |
| Grip                 | MicroFoam   |
| Gauge                | 15  |
| Cuff                 | Knit Wrist  |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit,<br>Touchscreen Compatible   |
| Certifications       | 21 CFR, CFIA, Silicone Free,<br>Latex Free        |
| Product Circularity  | Reusable / Launderable<br>Recycled via Terracycle |

#### Performance Data

| ANSI Abrasion Level | 4     |
|---------------------|-------|
| ANSI Puncture Level |       |
| ANSI Impact Level   |       |
| EN 388              | 4131X |
| EN 407              |       |

### **Care Instructions**











Wash

Water Temp 40°C