



SPECIFICATION SHEET

STYLE: CCNCHR-62RB



Technical Data

Color	Royal
Sizes Available	XS-6XL
Packaging	Case
Packed	20/Case
Case Dimensions (cm)	61.00 x 40.60 x 30.50
Case Weight (kg)	0.68
Country of Origin	China
Clothing Type	Coveralls
Fabric	Auto Grid
Closure	Double Pull Zipper
Construction	ESD Safe, Low-Lint
Certifications	--
Product Circularity	Reusable / Launderable

Uniform Technology™

Auto Grid Paint Powder Coating Coverall

- Auto Grid Fabric - 99% Polyester / 1% Carbon
- Raglan sleeves for more movement
- Extra wide front facing with double pull zipper to protect clothing worn under coveralls
- Inside left breast pocket and back hip pocket with flap to carry essentials
- Hidden snaps and tabs on inside back waist for additional sizing
- Black tricot vents on full upper back, sleeve outseam, leg inseam and leg back to allow for maximum breathability
- Elastic sleeve opening with hidden snap closure for easy donning
- Pass through pockets side front with inside (modesty) flap
- Radio webbing loops on front sleeve seams and back right waist to hang tools

Performance Data

ISO Cleanroom	--
ANSI/ESD S20.20	--
Temperature Resistant	--
Static Control Property	Static Dissipative

Care Instructions

Our garments do not come wearer ready meaning they need to be laundered before an employee wears them in an ISO class cleanroom. Average wear and tear lifespan is 50-100 washes. Make sure all zippers and snaps are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (140°F). After drying tumble dry cold for 5 minutes. No iron.

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-27