



Technical Data

| Color | |
|----------------------|---------------|
| Sizes Available | |
| Packaging | |
| Packed | |
| Case Dimensions (cm) | |
| Case Weight (kg) | 0.00 |
| Hearing Style | |
| Protection Type | |
| EN 352 | |
| Construction | |
| Certifications | TAA Compliant |
| Product Circularity | |

Performance Data

| NRR Rating (ANSI S3.19-1974) | |
|------------------------------|-------|
| SNR Rating | |
| SLC 80 | |
| SLC 80 Class | Class |
| CSA Z94.2 | Class |
| | |

3M

Hearing Peltor, Earmuffs, Optime 1, 26Db, Helmet Mounted (H510P3E-405-GU)

- Reduces noise levels up to 28 dB
- Low-profile design combines easily with other safety equipment
- Sealing rings filled with a unique combination of liquid and foam
- Large space inside the cups helps minimise heat and moisture buildup
- Soft
- wide
- cushions help reduce pressure around the ears
- Cushions and inserts available as replacement Hygiene Kits
- Available in headband
- neckband
- helmet attached and Hi-Viz green models
- For moderate industrial noise
- such as workshops
- sheet-metal shops and printing works
- Use in outdoor activities
- including lawn mowing or hedge trimming