



ESD

Technical Data

Color	Black
Sizes Available	L-XL
Packaging	Case
Packed	50/Case
Case Dimensions (cm)	40.64 x 17.78 x 10.16
Case Weight (kg)	1.36
Country of Origin	Japan
Polymer	Polyurethane
Grip	Smooth
Cuff	Pinked
Length	10.25"
Powder	--
Thickness	7 Mil
Construction	Supported, ESD Safe
Certifications	TAA Compliant
Product Circularity	--

QRP® PolyTuff® ESD

Polyurethane Electrostatic Dissipative (ESD)
Solvent Glove with Cotton Lining - 10.25"

- Polyurethane coating offers superior chemical protection while delivering ESD resistance
- Static dissipative, surface resistance 103 – 107 ohms
- 100% cotton knit liner plus conductive fiber for extra comfort and protection
- High grip surface

Performance Data

ISO Cleanroom	--
Temperature Resistant	--
Static Control Property	Static Dissipative

Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-04