



SPECIFICATION SHEET

STYLE: GP8C



QRP® Qualatex®

Static Dissipative Vacuum Sealed Latex Finger
Cots ISO 5 (Class 100)

- Packaged for ISO 5 (Class 100) applications
- Unique, Stand-Up pouch for easy product identification
- Compliant with ASTM and IEST-RP-CC 005.3 standards
- Average surface resistance 10(7) Ohms per square unit
- For use with Class I and Class II static sensitive devices
- RoHS compliant
- P3 Polar Process
- ESD Safe to ANSO/ESD S20.20-2014
- Contains 100% natural latex which may cause allergic reactions

Technical Data

Color	Black
Sizes Available	S-XL
Packaging	Case
Packed	14400/Case
Case Dimensions (cm)	48.26 x 27.94 x 33.02
Case Weight (kg)	9.64
Country of Origin	Viet Nam
Polymer	Latex
Grip	Textured
Thickness	--
Powder	Powder Free
Construction	--
Certifications	--
Product Circularity	--

Performance Data

ISO Cleanroom	ISO 5 (Class 100)
Temperature Resistant	--
Static Control Property	Static Dissipative

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-08-18