

SPECIFICATION SHEET

STYLE: GP555



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Nitrile Coated Foam Grip on Palm & Fingers -Touchscreen Compatible

- Nitrile coated foam grip palm and fingers provide a controlled grip in dry, and slightly oily conditions
- MicroFoam Nitrile stays flexible in hot and cold conditions
- Reinforced thumb crotch provides longer wear life and increased
- Touchscreen compatible to allow the user to operate a touchscreen phone or device without removing gloves
- Knit wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring











Technical Data

| Color | Gray |
|----------------------|--|
| Sizes Available | S-2XL |
| Packaging | Pair Bagged Retail Ready |
| Packed | 144 Pair/Case |
| Case Dimensions (cm) | 56.00 x 28.00 x 36.00 |
| Case Weight (kg) | 10.90 |
| Country of Origin | China |
| Liner Material | HPPE |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Foam |
| Gauge | 18 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit, Reinforced Thumb Crotch, Touchscreen Compatible, ESD Safe |
| Certifications | |
| Product Circularity | Recycled via Terracycle Reusable / Launderable |

Performance Data

| Cut Level | A5 |
|---------------------------------|-------|
| ANSI Abrasion Level | 6 |
| ANSI Puncture Level | 2 |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 4X41E |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions









