



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with
Foam Nitrile Coated Grip on Palm & Fingers -
Touchscreen - 18 Gauge

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Nitrile is a synthetic rubber compound that offers excellent puncture, tear and abrasion resistance
- Foam Nitrile coatings are breathable and durable, designed with a cell structure that disperse fluids on contact for an improved grip
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Reinforcement - between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area.

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



Technical Data

| | |
|----------------------|--|
| Color | Salt & Pepper |
| Sizes Available | S-2XL |
| Packaging | Pair Bagged Retail Ready |
| Packed | 6 Dozen/Case |
| Case Dimensions (cm) | 35.00 x 28.00 x 26.00 |
| Case Weight (kg) | 3.20 |
| Liner Material | PolyKor |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Foam |
| Gauge | 18 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit, Touchscreen Compatible, Reinforced Thumb Crotch, ESD Safe |
| Certifications | -- |
| Product Circularity | Recycled via Terracycle Reusable / Launderable |

Performance Data

| | |
|---------------------------------|-------|
| Cut Level | A4 |
| ANSI Abrasion Level | 5 |
| ANSI Puncture Level | 3 |
| ANSI Impact Level | -- |
| ANSI Contact Heat Level | -- |
| EN 388 | 4X42D |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |

Care Instructions

