



# SPECIFICATION SHEET

STYLE: S10HTP/2BK-EW-ES6-T



## Technical Data

|                      |                                                |
|----------------------|------------------------------------------------|
| Color                | Black                                          |
| Sizes Available      | 18, 22                                         |
| Packaging            | Bulk Banded                                    |
| Packed               | 72/Case                                        |
| Case Dimensions (cm) | 50.80 x 35.56 x 27.94                          |
| Case Weight (kg)     | 11.00                                          |
| Country of Origin    | United States                                  |
| Liner Material       | High-Tenacity Polyester, ATA Fiber Technology  |
| Top of Arm           | Non-Slip                                       |
| Finger & Thumb       | Thumb Hole                                     |
| Ply                  | Single-Ply                                     |
| Lining               | --                                             |
| Construction         | Machine Knit                                   |
| Certifications       | TAA Compliant                                  |
| Product Circularity  | Recycled via Terracycle Reusable / Launderable |

## Kut Gard®

### Single-Ply ATA® / High Tenacity Polyester Blended Sleeve with Thumb Hole - Wide Width

- Proprietary ATA® Technology provides ANSI A2 cut protection and outstanding wearer comfort
- Three widths are available, narrow, standard and wide for a personalized fit; great for workers with thin to bulky arms
- Color-coded overedge indicates width of sleeve, red indicates narrow, yellow indicates standard and green indicates wide, for ease in sorting
- No-Slip elastic at the top of the sleeve helps to keep sleeves in place
- Knit wrist stays in place and is less binding than elastic wrist, offering cut protection from the top to bottom
- ASTM D3884-09 Level 2 abrasion resistance

## Applications

- High Cut Protection and Performance
- Machine Operations
- Metal Fabrication
- Plastic Molding

## Performance Data

|                                 |    |
|---------------------------------|----|
| Cut Level                       | A2 |
| ANSI Puncture Level             | -- |
| ANSI Contact Heat Level         | -- |
| ASTM F1358 Vertical Flame Level | -- |

## Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-04-03