



ESD

Technical Data

| | |
|----------------------|------------------------|
| Color | Blue |
| Sizes Available | XS-5XL |
| Packaging | Case |
| Packed | 1/Case |
| Case Dimensions (cm) | 61.00 x 40.60 x 30.50 |
| Case Weight (kg) | 0.91 |
| Country of Origin | Mexico |
| Clothing Type | Lab Coats |
| Fabric | Staticon |
| Closure | Snap |
| Construction | ESD Safe |
| Certifications | TAA Compliant |
| Product Circularity | Reusable / Launderable |

Uniform Technology™ Staticon Long ESD Labcoat

- Staticon Fabric - 98% Polyester / 2% Carbon
- Lapel collar
- Three patch pockets
- Snaps at front opening
- Grounding snap on waist pocket
- Pen slot on breast pocket
- Side slits on the bottom of each side for pocket access
- Standard hem closure
- ESD safe compliance to ANSI/ESD S20.20-2014 - Groundable Static Control Garment

Performance Data

| | |
|-------------------------|--|
| ISO Cleanroom | -- |
| ANSI/ESD S20.20 | Groundable Static Control Garment < 1x10 ⁹ Ω Point to groundable point |
| Temperature Resistant | -- |
| Static Control Property | Static Dissipative |

Care Instructions

Our garments do not come wearer ready meaning they need to be laundered before an employee wears them in an ISO class cleanroom. Average wear and tear lifespan is 50-100 washes. Make sure all zippers and snaps are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (140°F). After drying tumble dry cold for 5 minutes. No iron.

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-04-03