

SPECIFICATION SHEET STYLE: S10HTP/2BK-ES6





Single-Ply ATA® / High Tenacity Polyester Blended Sleeve

- Proprietary ATA® Technology provides ANSI A2 cut protection and outstanding wearer comfort
- Three widths are available, narrow, standard and wide for a personalized fit; great for workers with thin to bulky arms
- Color-coded overedge indicates width of sleeve, red indicates narrow, yellow indicates standard and green indicates wide, for ease in sorting
- No-Slip elastic at the top of the sleeve helps to keep sleeves in place
- Knit wrist stays in place and is less binding than elastic wrist, offering cut protection from the top to bottom
- ASTM D3884-09 Level 2 abrasion resistance

Applications

- High Cut Protection and Performance
- Machine Operations
- Metal Fabrication
- Plastic Molding



Technical Data

Color	Black
Sizes Available	18, 22
Packaging	Bulk Banded
Packed	72/Case
Case Dimensions (cm)	50.80 x 35.56 x 27.94
Case Weight (kg)	9.96
Country of Origin	United States
Liner Material	High-Tenacity Polyester, ATA Fiber Technology
Top of Arm	Non-Slip
Ply	Single-Ply
Lining	
Construction	Machine Knit
Certifications	TAA Compliant
Product Circularity	Recycled via Terracycle Reusable / Launderable

Performance Data

Cut Level	A2
ANSI Puncture Level	
ANSI Contact Heat Level	
ASTM F1358 Vertical Flame Level	

Care Instructions









