



Technical Data

| | |
|----------------------|--|
| Color | -- |
| Sizes Available | S-5X |
| Packaging | Bagged Each |
| Packed | 6/Case |
| Case Dimensions (cm) | 72.00 x 45.00 x 32.00 |
| Case Weight (kg) | 15.00 |
| Country of Origin | China |
| Fabric | Cellulose, Modacrylic |
| Weight | -- |
| Closure | Zipper & Snap |
| Total Pockets | 4 |
| Pocket Type | Internal Pocket, Mic Tab, Pen Pocket, Waist Pocket |
| Construction | Ripstop, Water Repellent |
| Certifications | NFPA 70E, UL Certified, ASTM F1506, NFPA 2112 |
| Product Circularity | Reusable / Launderable |

Bisley®

AR/FR Ripstop Insulated Parka with Navy Bottom - Industrial Wash Durable

- ANSI 107 Type R Class 3
- ARC Rating: PPE 4 ATPV 40.0 cal/cm2
- 7oz FR inherent ripstop outer fabric for added durability
- 14oz FR modacrylic/cotton insulation, for extra warmth in extreme cold conditions
- High tenacity Aramid thread to withstand stress during fire exposure and high temperatures
- 1% Antistatic to help inhibit electrostatic discharge (ESD)
- Detachable insulated hood with contrast lining
- 2 in silver FR reflective H-tape for optimal visibility
- Navy bottom helps hide dirt
- Twin waist patch pockets with flap closures
- One internal pocket
- Mic tabs and pen pocket at shoulders for convenience
- Two piece structured, contrast color collar
- Melamine FR buttons, and FR closures
- Renewably sourced, non-fluorinated water repellent treatment
- Dual-certified to NFPA 70E (ASTM F1506) and NFPA 2112-2023 standards
- OEKO-TEX® Standard 100

Performance Data

| | |
|-----------------|----|
| PPE Category | 4 |
| ANSI Type/Class | R3 |
| CSA Class | -- |
| CSA Level | -- |

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-02