

SPECIFICATION SHEET

STYLE: 19-D340OR



G-Tek® ECO Series™

Hi-Vis Seamless Knit Dyneema® Diamond 2.0 Blended Glove with Nitrile Coated Foam Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- Dyneema® Diamond 2.0 & Spandex shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Dyneema® bio-based fibers equates to 450g of CO2 emissions reduction per pair when compared to traditional Dyneema® fibers
- Foam Nitrile coatings are breathable and durable, designed with a cell structure that disperse fluids on contact for an improved grip
- Knit Wrist helps prevent dirt and debris from entering the glove
- Hi-Vis coloring makes this product very easy to see

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



Technical Data

| Color | Hi-Vis Orange |
|----------------------|---|
| Sizes Available | XS-XXL |
| Packaging | Pair Bagged Retail Ready |
| Packed | 6/Case |
| Case Dimensions (cm) | 30.00 x 32.00 x 40.00 |
| Case Weight (kg) | 6.80 |
| Country of Origin | China |
| Liner Material | Dyneema Diamond 2.0 Technology |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Foam |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | 21 CFR |
| Product Circularity | Recycled via Terracycle Reusable / Launderable Contains Bio-Based Materials |

Performance Data

| Cut Level | A4 |
|---------------------------------|--------|
| ANSI Abrasion Level | 6 |
| ANSI Puncture Level | 4 |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 4X43DX |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

