PIP

SPECIFICATION SHEET STYLE: 9100-2170D



PIP[®] AR/FR Dual Certified Coverall - 13.2 Cal/cm2

- 9oz 90% cotton/10% Nylon
- PPE22, ATPV 13.2 cal/cm2
- Aramid high tenacity FR thread
- No metal pieces on the garment
- Bar-tacked at all stress points
- Protective stand-up collar with hook & loop closure
- Storm guard with hook & loop closure
- Action back for mobility
- Side elasticized waist
- FR rib knit cuffs
- Hook & loop on bottom
- 2 waist patch pockets with side access
- UL Certified
- NFPA 2112-2023
- NFPA 70E, ASTM F 1506
- CAN/CGSB 155.20, CAN/CGSB 155.22
- OSHA 29 CFR1910.269
- EN ISO11611, EN ISO11612, EN ISO14116

Applications

- Electrical Contractors
- Utility Work



Technical Data

Color	Navy, Light Gray
Sizes Available	S-5X
Packaging	Bagged Each
Packed	18/Case
Case Dimensions (cm)	41.00 x 41.00 x 51.00
Case Weight (kg)	23.00
Country of Origin	China
Clothing Type	Coveralls
Fabric	Cotton, Nylon
Weight	9oz
Hide	
Total Pockets	2
Closure	Hook and Loop
Construction	
Certifications	OSHA 29 CFR 1910, NFPA 70E, UL Certified, ASTM F1506, NFPA 1975, NFPA 2112
Product Circularity	

Performance Data

PPE Category	2
ARC Rating	13.2 cal/cm2
ANSI Type/Class	

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU*

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-02