

SPECIFICATION SHEET STYLE: 9100-2160D



PIP®

AR/FR Dual Certified Coverall - 9.2 Cal/cm2

- 7oz 90% Cotton 10% Nylon
- PPE Level 2, ATPV 9.2 cal/cm2
- · Aramid high tenacity FR thread
- No metal pieces on the garment
- · Bar-tacked at all stress points
- · Protective stand-up collar with hook & loop closure
- Storm guard with hook & loop closure
- Action back for mobility
- Side elasticized waist
- · FR rib knit cuffs
- Hook & loop on bottom
- 2 waist patch pockets with side access
- UL Certified
- NFPA 2112-2023
- NFPA 70E, ASTM F 1506
- CAN/CGSB 155.20, CAN/CGSB 155.22
- OSHA 29 CFR1910.269
- EN ISO11611, EN ISO11612,, EN ISO14116,

Applications

- Electrical Contractors
- Utility Work



Technical Data

Color	Navy
Sizes Available	S-5X
Packaging	Bagged Each
Packed	18/Case
Case Dimensions (cm)	41.00 x 54.00 x 51.00
Case Weight (kg)	23.00
Country of Origin	China
Clothing Type	Coveralls
Fabric	Cotton, Nylon
Weight	7oz
Hide	
Closure	Hook and Loop
Construction	
Certifications	OSHA 29 CFR 1910, NFPA 70E, UL Certified, ASTM F1506, NFPA 1975, NFPA 2112
Product Circularity	

Performance Data

PPE Category	2
ARC Rating	9.2 cal/cm2
ANSI Type/Class	

Care Instructions



Only synthetic detergents should be used on this AR/FR garment. Do not use bleach, starch, fabric softeners or detergents containing hydrogen peroxide on this garment as they could negatively affect the protective properties.