



## G-Tek® ECO Series™

Seamless Knit Dyneema® Phoenix Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- Spun Dyneema® Phoenix & Spandex shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Bio-Based Dyneema fiber provides same performance & protection, while providing lower carbon footprint
- Dyneema® bio-based fibers equates to 450g of CO2 emissions reduction per pair when compared to traditional Dyneema® fibers
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove

## Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



## Technical Data

|                      |   |
|----------------------|---|
| Color                | White   |
| Sizes Available      | XS-2XL  |
| Packaging            | Pair Bagged Retail Ready  |
| Packed               | 6 Dozen/Case  |
| Case Dimensions (cm) | 30.00 x 32.00 x 36.00   |
| Case Weight (kg)     | 4.90  |
| Country of Origin    | Viet Nam  |
| Liner Material       | Dyneema Phoenix   |
| Coating              | Polyurethane  |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers  |
| Grip                 | Flat  |
| Gauge                | 13  |
| Cuff                 | Knit Wrist  |
| Impact Protection    | --  |
| Construction         | Coated Seamless Knit  |
| Certifications       | --  |
| Product Circularity  | Reusable / Launderable<br>Contains Bio-Based Materials<br>Recycled via Terracycle |

## Performance Data

|                                 |        |
|---------------------------------|--------|
| Cut Level                       | A2     |
| ANSI Abrasion Level             | 3      |
| ANSI Puncture Level             | 3      |
| ANSI Impact Level               | --     |
| ANSI Contact Heat Level         | --     |
| EN 388                          | 4X42BX |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-05-20