

# SPECIFICATION SHEET

STYLE: 19-D327



# G-Tek® 3GX®

Seamless Knit Dyneema® Diamond Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- · Seamless construction offers increased comfort and breathability
- Dyneema® Diamond & Nylon shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

# **Applications**

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging









### **Technical Data**

| Color                | Gray  |
|----------------------|---|
| Sizes Available      |   |
| Packaging            | Pair Bagged Retail Ready                          |
| Packed               |   |
| Case Dimensions (cm) | 30.00 x 32.00 x 36.00                             |
| Case Weight (kg)     | 5.60  |
| Country of Origin    | Viet Nam  |
| Liner Material       | Dyneema Diamond Technology                        |
| Coating              | Polyurethane                                      |
| Coating Color        | Gray  |
| Coating Coverage     | Palm & Fingers                                    |
| Grip                 | Flat  |
| Gauge                | 15  |
| Cuff                 | Knit Wrist  |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit                              |
| Certifications       |   |
| Product Circularity  | Reusable / Launderable<br>Recycled via Terracycle |

## **Performance Data**

| Cut Level                       | A3    |
|---------------------------------|-------|
| ANSI Abrasion Level             | 6     |
| ANSI Puncture Level             | 4     |
| ANSI Impact Level               |       |
| ANSI Contact Heat Level         |       |
| EN 388                          | 4X43C |
| ASTM F1358 Vertical Flame Level |       |
| EN 407                          |       |

### **Care Instructions**









