



G-Tek® KEV™

Seamless Knit Kevlar® Blended Glove with Foam Nitrile Coating on Palm & Fingers

- Seamless knit construction provides comfort without sacrificing dexterity
- Kevlar® fiber shell provides high tensile strength relative to its weight, is inherently cut resistant and will not melt, ignite or conduct electricity
- Foam Nitrile coatings are breathable and durable, designed with a cell structure that disperse fluids on contact for an improved grip
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Launderable for extended life and to reduce replacement costs

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



Technical Data

| | |
|----------------------|---|
| Color | Yellow |
| Sizes Available | S-2XL |
| Packaging | Pair Bagged Retail Ready |
| Packed | 6 Dozen/Case |
| Case Dimensions (cm) | 43.00 x 31.00 x 28.00 |
| Case Weight (kg) | 5.90 |
| Liner Material | Kevlar |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Foam |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit |
| Certifications | -- |
| Product Circularity | Recycled via TerraCycle Reusable / Launderable |

Performance Data

| | |
|---------------------------------|--------|
| Cut Level | A7 |
| ANSI Abrasion Level | 4 |
| ANSI Puncture Level | 2 |
| ANSI Impact Level | -- |
| ANSI Contact Heat Level | 2 |
| EN 388 | 4X32FX |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |

Care Instructions

