

SPECIFICATION SHEET STYLE: GP16645LG



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Hi-Vis coloring makes this product very easy to see
- Color coded hems for easy size identification

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and
- Shipping, Receiving and Packaging



Technical Data

| Color | Hi-Vis Yellow |
|----------------------|---|
| Sizes Available | XS-2XL |
| Packaging | Pair Bagged Retail Ready |
| Packed | 6 Dozen/Case |
| Case Dimensions (cm) | 38.00 x 31.00 x 27.00 |
| Case Weight (kg) | 4.60 |
| Country of Origin | China |
| Liner Material | PolyKor |
| Coating | Polyurethane |
| Coating Color | Gray |
| Coating Coverage | Palm & Fingers |
| Grip | Flat |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | Silicone Free |
| Product Circularity | Recycled via Terracycle Reusable / Launderable |

Performance Data

| Cut Level | A5 |
|---------------------------------|--------|
| ANSI Abrasion Level | 3 |
| ANSI Puncture Level | |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 4X42EX |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions











KEY: **()** Made from recycled or bio-based **()** Launderable **()** Recyclable via TerraCycle **()**