

SPECIFICATION SHEET STYLE: 713HGBU



G-Tek® PosiGrip®

Seamless Knit Polykor Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- Polykor blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



Technical Data

| Color | Black |
|----------------------|---|
| Sizes Available | S-XL |
| Packaging | Bulk Pack |
| Packed | 10/Case |
| Case Dimensions (cm) | 52.58 x 28.45 x 29.97 |
| Case Weight (kg) | 6.80 |
| Country of Origin | Sri Lanka |
| Liner Material | PolyKor |
| Coating | Polyurethane |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Flat |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | |
| Product Circularity | Reusable / Launderable Recycled via Terracycle |

Performance Data

| Cut Level | A1 |
|---------------------------------|--------|
| ANSI Abrasion Level | 4 |
| ANSI Puncture Level | |
| ANSI Impact Level | |
| ANSI Contact Heat Level | |
| EN 388 | 4343AX |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions









