PIP

ANSI/ISEA 105-2024
A6 4 3 | A6 CUT | 4 ABR | 3 PUN | 1 | EN388 4X42F | EN407 X1XXXX

Technical Data

Color	Green
Sizes Available	XS-3XL
Packaging	Bulk Pack
Packed	12/Case
Case Dimensions (cm)	50.00 x 28.00 x 48.00
Case Weight (kg)	12.10
Country of Origin	Pakistan
Liner Material	Aramid, PolyKor
Coating	Nitrile
Coating Color	Black
Coating Coverage	Palm & Fingers
Grip	Foam
Gauge	13
Palm	--
Back	--
Cuff	Knit Wrist
Impact Protection	--
Construction	Coated Seamless Knit
Certifications	--
Product Circularity	--

G-Tek® PosiGrip®
AR Seamless Knit PolyKor®/Aramid Blend Glove with Nitrile Foam Coated Grip on Palm & Fingers

- Seamless knit construction provides comfort without sacrificing dexterity
- PolyKor/Aramid blended shell is lightweight, has excellent dexterity, tactile sensitivity and cut resistance while also providing protection in heat resistant applications, where sparks and minor flames are present
- Foam Nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Arc rating: ATPV 7.6 cal/cm2
- EN 407 tested Contact Heat Level 2
- Knit Wrist helps prevent dirt and debris from entering the glove

Applications

- Installation, Maintenance, and Repairing Electrical Distribution and Transmission System
- Framing and Setting Poles and Meters
- Attaching and Testing Grounding Devices to Remove Electrical Hazards

Performance Data

Cut Level	A6
ANSI Abrasion Level	4
ANSI Puncture Level	3
ANSI Impact Level	--
PPE Category	1
ANSI Contact Heat Level	--
EN 388	4X42F

Care Instructions

Machine Wash | Water Temp 40°C | Do Not Bleach | Hang Dry