



### Bisley®

#### AR/FR Dual-Certified Insulated Parka Jacket - 33.3 cal/cm2

- ARC Rating: PPE 3 ATPV 33.3 cal/cm2
- Shell: 88% Cotton 12% Nylon
- 14oz FR modacrylic/cotton insulation, for extra warmth in extreme cold conditions
- High tenacity Aramid thread to withstand stress during fire exposure and high temperatures
- 2 in FR reflective tape X back for optimal visibility
- Dual-certified to NFPA 70E (ASTM F1506) and NFPA 2112-2023 standards
- Protective stand-up collar with snap closure
- Shaped, detachable hood with snaps closure
- Internal aramid rib cuff hidden inside sleeve
- Adjustable sleeve tab with hook and loop closure
- 2 waist patch pockets with single mitred pocket flap, flap with velcro closure
- 1 pen pocket on left sleeve



### Technical Data

Color	Blue/Royal
Sizes Available	XS-5XL
Packaging	--
Packed	--
Case Dimensions (cm)	72.00 x 45.00 x 32.00
Case Weight (kg)	13.10
Fabric	Cotton, Nylon
Weight	--
Closure	Zipper & Snap
Total Pockets	3
Pocket Type	Pen Pocket , Waist Pocket, Mic Tab
Construction	X-Back
Certifications	NFPA 70E, UL Certified, ASTM F1506, NFPA 2112, CSA Z96 Compliant
Product Circularity	Reusable / Launderable

### Performance Data

PPE Category	3
ANSI Type/Class	--
CSA Class	Class 2
CSA Level	Level 2/FR

### Care Instructions



Machine Wash



Water Temp 40°C



Tumble Dry



Low Heat



Do Not Dry-clean

Only synthetic detergents should be used on this AR/FR garment. Do not use bleach, starch, fabric softeners or detergents containing hydrogen peroxide on this garment as they could negatively affect the protective properties.

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2026-02-01