



G-Tek®

G-Tek® 13G AR seamless knit glove with Polykor®/aramid blended liner and foam neoprene coating on palm & fingers - CUT D

- Seamless knit construction provides comfort without sacrificing dexterity.
- PolyKor® blended shell with Aramid is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance while providing protection in heat resistant applications, where sparks and heat are present.
- Black neoprene foam coating provides a secure grip in dry, wet and oily conditions, infused with thousands of tiny suction cup pockets that create a vacuum effect that dispenses fluids away on contact.
- 13 Gauge.
- ARC Rating: ATPV 13 cal/cm2
- EN 407 tested Limited Flame Spread Level 4



Technical Data

Color	Yellow
Sizes Available	--
Packaging	--
Packed	--
Case Dimensions (cm)	--
Case Weight (kg)	0.00
Country of Origin	--
Liner Material	Aramid, PolyKor
Coating	Neoprene
Coating Color	Black
Coating Coverage	Palm & Fingers
Grip	Foam
Gauge	13
Cuff	Knit Wrist
Impact Protection	--
Construction	Seamless Knit
Certifications	TAA Compliant
Product Circularity	--

Performance Data

Cut Level	--
ANSI Abrasion Level	--
ANSI Puncture Level	--
ANSI Impact Level	--
ANSI Contact Heat Level	--
EN 388	3X42D
ASTM F1358 Vertical Flame Level	--
EN 407	4131XX

Care Instructions

It is advisable to clean the gloves in temperate water with a maximum temperature of 40°C. A mild non-ionic detergent should be used. A drying time of 5-10 minutes should be used. Low temperature tumble drying - maximum temperature 140°F (60°C)